

MATERIAL SAFETY DATA SHEET

SECTION I

IDENTITY: E-Z PATCH® # 4 F.S. Pool Tile Cement Dry Mix

SECTION II - Hazardous Ingredients/Identity Information

Hazardous Components: Portland Cement (CAS 65997-15-1)

OSHA PEL: 50 Mppcf

ACGIH TLV: 10mg/m³ - TWA

Hazardous Components: Limestone (CAS 474-34-1)

OSHA PEL: 5mg/m³ - (respirable): 15mg/m³ (total dust)

ACGIH TLV: 10mg/m³ - TWA

Hazardous Components: Aluminum Oxide (CAS 1344-28-1)

OSHA PEL: 10, 5mg/m³ respirable dust

ACGIH TLV: 10 mg/m³

SECTION III - Physical/Chemical Characteristics

Boiling Point: NA

Specific Gravity: 3.1

Vapor Pressure: NA

Melting Point: ND

Vapor Density: NA

Evaporation Rate: NA

Solubility in water: < 1%

Appearance & Odor: White-No Odor

SECTION IV - Fire and Explosion Hazard Data

Flash Point: NA

Extinguishing Media: NA

Special Fire Fighting Procedures: NA

Unusual Fire and Explosion Hazards: NA

SECTION V - Emergency Overview

May cause irritation to eyes, skin and upper respiratory tract. No unusual fire or spill hazard. Off-white powder.

Potential Health Effects:

EYES: May cause irritation, especially when wet.

SKIN: May irritate skin.

INHALATION: May cause upper respiratory irritation.

SECTION VI - First Aid Measures

EYES: Flush eyes with plenty of water for at least 15 minutes. If irritation persists, consult a physician.

SKIN: Wash with soap and warm water. If irritation develops, consult a physician

INHALATION: Remove victim to fresh air. If not breathing, give artificial respiration. Get immediate medical attention

NA=Not Applicable

ND=Not Determined

Date Prepared: 06-07-96

Disclaimer: E-Z Products believes the information contained herein is accurate. However, E-Z Products makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained by the use thereof. E-Z Products assumes no responsibility for injury from the use of the product described herein.