



CLEAR FLEXIBLE VINYL REPAIR SEALANT

No patch usually needed!

E-Z INSTRUCTIONS:

1. Repairs may be done underwater or above water. Surface must be clean.
2. Extrude E-Z Patch® 28 onto any rip, cut or hole area on Vinyl Liner or Pool/ Spa Cover.
3. Using wet fingers, with light pressure, even out E-Z Patch® 28 leaving 1/8" thickness and "featheredge" the edges flush with surface.
4. When a patch is needed due to heavy water flow, large cuts or rips and also for large repairs done at seams, use the enclosed clear vinyl liner patch.
5. A complete cure takes 3 to 5 days (must wait for complete cure before running pool vacuum). You may swim immediately after repair and it usually withstands physical contact after setting overnight.
6. If you need extra clear vinyl patches, E-Z Patch® 29 (sold separately) contains ten 5" x 5 1/2" sheets of clear vinyl patches.

View our instructional repair video showing how to do this repair at www.e-zpatch.com

E-Z ANSWERS to some Frequently Asked Questions

- **Product will cure faster in hotter weather, slower in cooler weather**
- **Product is best stored between 40 degrees F and 90 degrees F**
- **Product application is best when water temperature is above 50 degrees F**
- **Product also bonds to PVC plastic, Masonry, Fiberglass, Metal and Wood.**

WARNING: FLAMMABLE, DO NOT USE NEAR IGNITION SOURCES. DO NOT STORE NEAR HEAT OR FLAME. CONTAINS CYCLOHEXANONE, MEK, TOLUENE & V. M.& P. NAPHTHA. USE IN AREAS WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. IF INGESTED, DO NOT INDUCE VOMITING AND CALL A PHYSICIAN IMMEDIATELY. IN CASE OF CONTACT WITH EYES, IMMEDIATELY FLUSH WITH WATER FOR 15 MIN. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. UNCURED PRODUCT MAY IRRITATE THE SKIN. IF NEEDED, TO CLEAN FROM SKIN, USE MINERAL SPIRITS AND THEN WASH SKIN WITH SOAP AND WATER. PRODUCT USUALLY DOES NOT ADHERE TO SKIN IF SKIN IS WET AND ONLY LIGHT PRESSURE IS USED.

KEEP OUT OF THE REACH OF CHILDREN