



## UNDERWATER WHITE POOL TILE GROUT & SET OR ABOVE WATER GROUT FAST SET REPAIRS

### E-Z INSTRUCTIONS:

1. Only dry clay tiles must be soaked first in water for 10 – 15 minutes.
2. Remove all loose material or grout.
3. Add water to **E-Z PATCH® 4 F.S. DRY CEMENT MIX** (enough to be used within 5 – 10 minutes. Mix until you get the consistency of “mashed potatoes”.
4. **SETTING & GROUTING TILE UNDERWATER:** Place the wet mix of **E-Z PATCH® 4 F.S.** into a baggie. Underwater, apply to back of tile and firmly set in place. Completely fill area to be grouted. Using a sponge, wipe off excess grout leaving grout joint full and flush.
5. **GROUTING ABOVE WATER:** Completely fill area to be grouted. Using a sponge, lightly wipe off excess grout leaving joint full and flush. When dry, remove any excess grout residue “haze” off of the tile.

**Allow 4 hours set time before swimming**

**To make a Custom Color with any of our cement type repair supplies, use any cement dye.**

**View our instructional repair video showing how to do this repair at [www.e-zpatch.com](http://www.e-zpatch.com)**

### E-Z ANSWERS to some Frequently Asked Questions

- **Fast Set formulas do not require Liquid Bonder**
- **Product will cure faster in hotter weather, slower in cooler weather**
- **Product is best stored between 30 degrees F and 110 degrees F**

**WARNING:** CONTAINS CEMENT, AN ALKALINE SUBSTANCE IRRITATING TO EYES AND SKIN. SHOULD PRODUCT CONTACT EYES, FLUSH THEM IMMEDIATELY AND REPEATEDLY WITH WATER AND CALL A PHYSICIAN. DO NOT TAKE INTERNALLY. IN CASE OF SKIN CONTACT, RINSE IMMEDIATELY WITH WATER. USE OF RUBBER GLOVES IS RECOMMENDED.

**KEEP OUT OF THE REACH OF CHILDREN**