



FAST SET GRAY ANCHORING CEMENT

RAPID SETTING EXPANSIVE ANCHORING CEMENT FOR SETTING BOLTS, POSTS, HANDRAILS, MACHINERY, FENCES - ALMOST ANYTHING TO BE ANCHORED IN CONCRETE.

E-Z INSTRUCTIONS:

1. Clean oil, dust or loose debris from sides of hole to be filled and dampen surface slightly. Make sure hole is large enough to allow cement to flow easily around metal object.
2. Add water to **E-Z PATCH® 8 DRY CEMENT MIX** and mix it into a slightly pour-able consistency enough to be used within 5 minutes. Make sure the metal object is already in place and hold in place until material begins to stiffen. (If you are using this product for anchoring on vertical applications, you should mix it with less water so it is the consistency of “mashed potatoes”.)

Sets hard in about 15 minutes.

To make a Custom Color with any of our cement type repair supplies, use any cement dye.

View our instructional repair video showing how to do this repair at www.e-zpatch.com

E-Z ANSWERS to some Frequently Asked Questions

- **Liquid Bonder is not required for this repair kit.**
- **Product will cure faster in hotter weather, slower in cooler weather**
- **Product is best stored between 40 degrees F and 110 degrees F**

WARNING: CONTAINS CEMENT, AN ALKALINE SUBSTANCE IRRITATING TO EYES AND SKIN. SHOULD PRODUCT CONTACT EYES, FLUSH THEM IMMEDIATELY AND REPEATEDLY WITH WATER AND CALL A PHYSICIAN. DO NOT TAKE INTERNALLY. IN CASE OF SKIN CONTACT, RINSE IMMEDIATELY WITH WATER. USE OF RUBBER GLOVES IS RECOMMENDED.

KEEP OUT OF THE REACH OF CHILDREN