



Bulk Scrubber Pads for Tile Grouting Using E-Z Patch® 22 Silicone Rubber

E-Z INSTRUCTIONS:

1. Fill the grout joint or crack in the grout full & deep with E-Z Patch® 22 Neutral Cure Silicone Rubber.
2. Run finger or soft rubber trowel “float” over grout joints for 100% sealing to both sides of grout joint.
3. Submerge the **Scrubber Pad** in water, pour some **Liquid Dishwashing Soap** on the Scrubber Pad and immediately scrub off all excess silicone rubber.
4. Any other clean-up may be done with a paper towel and rubbing alcohol or mineral spirits.

**Do not allow liquid dishwashing soap or water to contact surfaces
to be grouted prior to installing silicone rubber.**

**Do not allow Silicone Rubber to skin over before removing any excess with
Scrubber Pads (about 1-5 minutes, depending on the temperature).**

View our instructional repair video showing how to do this repair at www.e-zpatch.com

E-Z ANSWERS to some Frequently Asked Questions

- **Silicone Rubber grouting is best done between 50 degrees F and 90 degrees F**
- **Silicone Rubber will skin over faster in hotter weather, slower in cooler weather**
- **Using Neutral Cure Silicone Rubber (E-Z Patch 22) is the best to use for flexible long lasting tile repairs**