



1 FS

WHITE OR COLORED POOL PLASTER REPAIR FOR UNDER WATER OR ABOVE WATER FAST SET REPAIRS

Before mixing and applying the repair material, make sure it is the right color and material match! It is sometimes hard to see exactly what the color will be from computer monitor screens.

Take a small amount of dry material out of the repair kit and mix with water to be the consistency of "Putty". Then, wet the existing surface that you are trying to match and compare the wet sample to the wet existing surface. If the material needs to be darker, add a very small amount of E-Z Patch Black Cement Dye and dry mix well. If the material needs to be lighter, add a very small amount of E-Z Patch Titanium Dioxide White Cement Colorant and dry mix well. Both colors are available on our website. You can also use any good cement dye. Repeat this process until the color match is satisfactory.

E-Z INSTRUCTIONS:

UNDER WATER REPAIRS:

1. Remove loose cement and chip area at least 3/8" deep. Make sure the edges are chipped straight down (not beveled or slanted). Clean the surface.
2. Add water sparingly to **E-Z PATCH® 1 F.S. DRY CEMENT MIX** and mix it into a very thick consistency enough to be used within 5 min. Use warm water for faster set and cold water to slow set.
3. Wait a couple of minutes (until the materials start to harden), place a little more than needed in your hand covering it inside of your fist or in a plastic bag. Apply at the repair area immediately pressing **E-Z PATCH® 1 F.S.** firmly with a trowel.
4. Slowly flatten smooth and flush with a trowel = flush with the existing plaster, clean edges and slowly back away from repair. Allow repair to set hard before swimming

ABOVE WATER REPAIRS:

1. Follow steps 1. & 2. above but do not wait and add a little more water.
- 2a. **CRACK REPAIRS:** Rub E-ZPATCH® 1 F.S. deep into crack and remove excess with a moist sponge.
- 2b. **CHIPS OR LARGER AREAS:** Firmly trowel E-Z PATCH® 1 F.S. filling the area = flush with the existing plaster. Trowel flat and smooth. Remove excess from edges with a moist sponge. Trowel once again for a finished repair. *Allow repair to set hard before filling pool.

To make a Custom Color with any of our cement type repair supplies, use any cement dye.

View our instructional repair video showing how to do this repair at www.e-zpatch.com

E-Z ANSWERS to some Frequently Asked Questions

- Fast Set formulas do not require Liquid Bonder
- Product will cure faster in hotter weather, slower in cooler weather
- Product is best stored between 30 degrees F and 110 degrees F

WARNING: CONTAINS CEMENT, AN ALKALINE SUBSTANCE IRRITATING TO EYES. SHOULD PRODUCT CONTACT EYES, FLUSH THEM IMMEDIATELY AND REPEATEDLY WITH WATER AND CALL A PHYSICIAN. DO NOT TAKE INTERNALLY. IN CASE OF SKIN CONTACT, RINSE IMMEDIATELY WITH WATER. USE OF RUBBER GLOVES IS RECOMMENDED.

KEEP OUT OF THE REACH OF CHILDREN